

OC-7N3008

8x10/100/1000Base-TX



Brief Introduction

OC-7N3008 is a new generation industrial Power over Ethernet Managed Switch with 8-Port 10/100/1000Base-TX that provide stable and reliable Ethernet transmission with high quality design and reliability. It is positioning in the broadband network intervention market, to offer and realize Ethernet data exchange, convergence and long-distance optical transmission with efficient bandwidth and reliable fiber optic network solutions for users. The industrial switch complies with various characteristics such as mini size, no fan, low power consumption, high reliability and stability, and easy to maintain.

With dual power input design, OC-7N3008 can offer redundant mechanisms for critical applications that need always-on connections. It can also operate either at standard operating temperature range -40 to 75°C. Housed in rugged DIN rail or wall mountable IP40 enclosures, these switches are perfect choices for harsh environments, such as industrial networking, intelligent transportation systems (ITS) and are also suitable for many military and utility market applications where environmental conditions exceed commercial product specifications.

Features

- > 8x10/100/1000Base-TX RJ45 ports
- > Support Auto-MDIX, and full/half duplex self-negotiation mode
- > Provide SC/FC/ST/LC interface fiber port, support single/dual fiber transmission
- > Support 9K bytes giant frame, compatible with various extension protocol
- > 4K MAC address table
- > Support IEEE802.3az energy efficient Ethernet technology
- > Support IPv6 Protocol
- > Electric 8KV surge protection, easy to use in outdoor environment
- > Complete status indicator, working state at a glance
- > Power input polarity protection design, no worry about wrong operation
- > Metal case, no fan design
- > Installation method: DIN rail /Wall mounting


Specification

Physical Port	
RJ45 Port and Speed	8x10/100/1000Base-TX
Parameters	
Ethernet Standards	IEEE802.3 IEEE802.3u IEEE802.3z IEEE802.3ab IEEE802.3x IEEE802.3az IEEE802.3Qad IEEE802.3ah IEEE802.1X IEEE802.1Q IEEE1588
Packet Buffer	2M
Maximum Packet Length	Up to 9K
MAC Address Table	4K
Transmission Mode	Store and Forward (full/half duplex mode)
Exchange Property	Delay time: < 7μs Backplane bandwidth: 20Gbps; Packet forwarding rate: 11.904Mpps
PoE (Optional)	
PoE Standard	8x IEEE 802.3af/IEEE 802.3at PoE
Power Budget	Max. PoE output power budget 30W

Specification

LED Indicator	
Power	Connect-always
RJ45	Link/Act: connect-always; data exchange-twinkle
Fiber	Link/Act: connect-always; data exchange-twinkle
Power Information	
Power Access Mode	Phoenix terminal, DC seat
Redundant Power Input	DC 9-56V
Overload Protection	Yes
Power Reverse	Support
Power Consumption	Full-load<15W
Physical Property	
Protection Grade	IP40 aluminum case
Cooling Mode	Natural cooling, no fan design
Dimensions	120mm x 90mm x 40mm (L x W x H)
Installation Mode	DIN rail/wall-mountable
Weight	600g (With PoE : 650g)
Working Environment	
Operating Temperature	-40°C~75°C
Operating Humidity	5%~90% non-condensing
Storage Temperature	-40°C~85°C
Warranty	
MTBF	500,000 hours
Defects Liability Period	3 years warranty, lifetime technical support
Certification Standard	
EMC	FCC Part15 Class A CE-EMC/LVD RoHS EN61000-4-2 (ESD), EN61000-4-3 (RS) EN61000-4-4 (EFT), EN61000-4-5 (Surge) EN61000-4-6 (CS), EN61000-4-8 EN61000-4-11
Vibration	IEC60068-2-6 -40~75°C High and Low Temperature Test IP40 Protection Test

Dimensions



Package List

- 1 x Fiber Switch
- 1 x Rail Mounting Kit
- 1 x Wall Mount Kit
- 1 x Warranty Card

Application



Order Information

Model Number	Port Description
OC-7N3202	Industrial Ethernet Switch, 2 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP
OC-7N3204	Industrial Ethernet Switch, 4 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP
OC-7N3008	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX
OC-7N3108	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX + 1 x 100/1000M Base-FX SFP
OC-7N3208	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP
OC-7N3202P	Industrial Ethernet Switch, 2 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP/ 2xPoE
OC-7N3204P	Industrial Ethernet Switch, 4 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP/ 4xPoE
OC-7N3008P	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX/ 8xPoE
OC-7N3108P	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX + 1 x 100/1000M Base-FX SFP/ 8xPoE
OC-7N3208P	Industrial Ethernet Switch, 8 x 10/100/1000M Base-TX + 2 x 100/1000M Base-FX SFP/ 8xPoE

*Fiber port can add 1*9 module. RJ45 port with PoE optional.